



THINKWELL HARDWARE & MACHINERY

Chain & Accessories

Thinkwell

CONTENT

02	• Introduction	
03	• ASTM80 Proofcoil Chain (G30)	
03	• ASTM80 High Test Chain (G43)	
03	• ASTM80 Transport Chain (G70)	
04	• NACM96 Proofcoil Chain (G30)	08 • DIN763 Link Chain
04	• NACM96 High Test Chain (G43)	08 • DIN764 Link Chain
04	• NACM96 Transport Chain (G70)	09 • DIN766 Link Chain
05	• Chain with Clevis Eye Grab Hooks on Both Ends (G43)	09 • Australian Short Link Chain
05	• Chain with Clevis Eye Grab Hooks on Both Ends (G70)	10 • Australian Medium Link Chain
06	• Grade 80 Alloy Chain	
07	• Grade 100 Alloy Chain	
07	• DIN5685A/C Short/Long Link Chain	11 • Tow Chain

COMPANY

Thinkwell

Thinkwell Hardware & Machinery CO.,Ltd is professional manufacturing facility providing Rigging Hardware ,Electric Line Pole power fittings, Trailer Hitches & Pulleys, Ornamental Wrought Iron, Container Fittings, Marine Hardware, Misc hardware and CNC parts .Our TK Brand is widely used in metallurgical machinery, electric power plants, coal operation , port operations, petrochemical industry, engineering, bridges, hydraulic engineering, shipping, cable-ways, overhead & fixed cranes along with portable mobile cranes etc.

Our International Sale Representatives work hand and hand with our inside sale representatives providing customer satisfaction through on-time manufacturing & delivery schedules, proficient documentation for hassle free service and handle questions with solutions for technical issues.

Thinkwell is a fully rounded service manufacture.

Introduction

The factory covers an area of 10,000 square meters and employs over 250 full-time staff . An Engineering department, Design department, Technical department with 15 Technicians and a QC/QA department overseeing all operations. Two forging workshops and a mold workshop.

Our basic equipment includes: 1000T/630T/400T/300T/160T forging machines, air hammers, heating furnace, rolling machines, tapping machines, blasting machines and so on. Our factory has joint venture relationships with the heat treatment factory ,milling factory and galvanizing plant. Through our QC program end users can enjoy safe, reliable and the highest quality TK Brand products they expect.

Thinkwell' s reputation is recognized through worldwide buyers for over 16+ years.

Production Equipments



Stamping Machine



CNC



Shot Blasting Machine



Forging Press



Cutting Machine



Hardness Machine



Forging Press



Tensile Testing Machine



Drilling Machine

Chain

1. ASTM80 Proofcoil Chain (G30)

G30 Chain
 Material: Q235
 Surface: Zinc Plating or Hot Dip Galvanized



Part No.	Size		Working Load Limit		Proof Load		Breaking Load		Weight Per 100' (KG)		Inside Length		Inside Width	
	(in.)	(mm)	(kg)	(lbs.)	(kn)	(lbs.)	(kn)	(lbs.)	(kg)	(lbs.)	(in.)	(mm)	(in.)	(mm)
TKC001	1/8	4.0	190	420	3.78	850	7.5	1,700	8.8	19	0.89	22.6	0.29	7.4
TKC002	3/16	5.5	360	800	7.11	1,600	14.2	3,200	18.3	40	0.95	24.1	0.40	10.2
TKC003	1/4	7.1	600	1,330	11.8	2,650	23.6	5,300	32.7	72	1.00	25.4	0.50	12.7
TKC004	5/16	8.7	910	2,000	17.8	4,000	35.6	8,000	48	106	1.10	27.9	0.50	12.7
TKC005	3/8	10.3	1,270	2,800	24.9	5,600	49.8	11,200	70.3	155	1.23	31.2	0.62	15.7
TKC006	1/2	13.5	2,190	4,800	42.9	9,650	85.8	19,300	123	271	1.53	28.9	0.80	20.3
TKC007	5/8	16.7	3,350	7,400	65.8	14,800	131.6	29,600	184	405	1.90	48.3	1.00	25.4
TKC008	3/4	19.8	4,700	10,400	92.5	20,800	185.0	41,600	264	582	2.15	54.6	1.12	28.4
TKC009	7/8	23.0	6,350	14,000	124.5	28,000	249.0	56,000	368	811	2.50	63.5	1.37	34.8
TKC010	1	26.5	8,400	18,600	165.4	37,200	330.8	74,400	474	1,045	2.75	69.9	1.50	38.1

2. ASTM80 High Test Chain (G43)

G43 Chain
 Material: Alloy Steel(20mn2)
 Surface: Zinc Plating or Hot Dip Galvanized



Part No.	Size		Working Load Limit		Proof Load		Breaking Load		Weight Per 100' (KG)		Inside Length		Inside Width	
	(in.)	(mm)	(kg)	(lbs.)	(kn)	(lbs.)	(kn)	(lbs.)	(kg)	(lbs.)	(in.)	(mm)	(in.)	(mm)
TKC011	1/4	7.1	1,180	2,600	19.1	4,300	34.5	7,750	36.3	80	0.86	21.8	0.40	10.2
TKC012	5/16	8.7	1,770	3,900	28.4	6,400	51.6	11,600	50.4	111	1.05	26.7	0.48	12.2
TKC013	3/8	10.3	2,450	5,400	39.6	8,900	72.0	16,200	72.6	160	1.19	30.3	0.58	14.7
TKC014	1/2	13.5	4,170	9,200	68.0	15,300	122.7	27,600	128.6	284	1.43	36.0	0.75	19.1

3. ASTM80 Transport Chain (G70)

G70 Chain
 Material: Alloy Steel(20mn2)
 Heat Treatment: Yes
 Surface: Zinc Plating or Hot Dip Galvanized



Part No.	Size		Working Load Limit		Proof Load		Breaking Load		Weight Per 100' (KG)		Inside Length		Inside Width	
	(in.)	(mm)	(kg)	(lbs.)	(kn)	(lbs.)	(kn)	(lbs.)	(kg)	(lbs.)	(in.)	(mm)	(in.)	(mm)
TKC015	1/4	7.1	1,430	3,150	27.8	6,300	56.0	12,600	34.0	75	0.86	21.8	0.45	11.4
TKC016	5/16	8.7	2,130	4,700	41.8	9,400	83.6	18,800	50.4	111	1.01	25.6	0.46	11.7
TKC017	3/8	10.3	2,990	6,600	58.7	13,200	117.4	16,400	71.0	156	1.19	30.2	0.55	14.0

4. NACM96 Proofcoil Chain (G30)

G30 Chain
 Material: Q235
 Surface: Zinc Plating or Hot Dip Galvanized



Part No.	Size		Working Load Limit		Proof Load		Breaking Load		Weight Per 100' (KG)		Inside Length		Inside Width	
	(in.)	(mm)	(kg)	(lbs.)	(kn)	(lbs.)	(kn)	(lbs.)	(kg)	(lbs.)	(in.)	(mm)	(in.)	(mm)
TKC018	1/8	4.0	180	400	3.6	800	7.2	1,600	9.0	19.8	0.94	23.9	0.25	6.4
TKC019	3/16	5.5	355	800	7.2	1,600	14.4	3,200	18.3	40.3	0.98	24.8	0.30	7.7
TKC020	1/4	7.0	580	1,300	11.6	2,600	23.2	5,200	30.0	66.1	1.24	31.5	0.38	9.8
TKC021	5/16	8.4	860	1,900	16.9	3,800	33.8	7,600	43.5	96	1.29	32.8	0.44	11.2
TKC022	3/8	10.0	1,200	2,650	23.6	5,300	47.2	10,600	64.5	142	1.38	35.0	0.55	14.0
TKC023	7/16	11.9	1,680	3,700	32.9	7,400	65.8	14,800	91.3	201	1.64	41.6	0.65	16.5
TKC024	1/2	13.0	2,030	4,500	40	9,000	80.0	18,000	110.0	242	1.79	45.5	0.72	18.2
TKC025	5/8	16.0	3,130	6,900	61.3	13,800	122.6	27,600	162.0	357	2.20	56.0	0.79	20.0
TKC026	3/4	20.0	4,800	10,600	94.3	21,200	188.6	42,400	254.0	560	2.76	70.0	0.98	25.0
TKC027	7/8	22.0	5,810	12,800	114.1	25,600	228.2	51,200	306.0	675	3.03	77.0	1.08	27.5
TKC028	1	26.0	8,140	17,900	159.1	35,800	318.2	71,600	419.0	924	3.58	90.9	1.25	31.7

5. NACM96 High Test Chain (G43)

G43 Chain
 Material: Alloy Steel(20mn2)
 Surface: Zinc Plating or Hot Dip Galvanized



Part No.	Size		Working Load Limit		Proof Load		Breaking Load		Weight Per 100' (KG)		Inside Length		Inside Width	
	(in.)	(mm)	(kg)	(lbs.)	(kn)	(lbs.)	(kn)	(lbs.)	(kg)	(lbs.)	(in.)	(mm)	(in.)	(mm)
TKC029	1/4	7.0	1,180	2,600	17.3	3,900	34.6	7,800	30.0	66.1	1.24	31.5	0.38	9.8
TKC030	5/16	8.4	1,770	3,900	26.0	5,850	52.0	11,700	45.0	99.2	1.29	32.8	0.44	11.2
TKC031	3/8	10.3	2,450	5,400	36.0	8,100	72.0	16,200	67.3	148	1.38	35.0	0.355	14.0
TKC032	1/2	13.5	4,170	9,200	61.3	13,800	122.6	27,600	116.0	256	1.79	45.5	0.72	18.2

6. NACM96 Transport Chain (G70)

G70 Chain
 Material: Alloy Steel(20mn2)
 Heat Treatment: Yes
 Surface: Zinc Plating or Hot Dip Galvanized



Part No.	Size		Working Load Limit		Proof Load		Breaking Load		Weight Per 100' (KG)		Inside Length		Inside Width	
	(in.)	(mm)	(kg)	(lbs.)	(kn)	(lbs.)	(kn)	(lbs.)	(kg)	(lbs.)	(in.)	(mm)	(in.)	(mm)
TKC033	1/4	7.1	1,430	3,150	28.0	6,300	56.0	12,600	30.0	66	1.24	31.5	0.38	9.8
TKC034	5/16	8.7	2,130	4,700	41.8	9,400	83.6	18,800	47.0	104	1.29	32.8	0.44	11.2
TKC035	3/8	10.3	2,990	6,600	58.7	13,200	117.4	16,400	69.0	152	1.38	35.0	0.55	14.0

Chain

7. Chain with Clevis/ Eye Grab Hooks on Both Ends (G43)

G43 Chain
 Material: Alloy Steel(20mn2)
 Surface: Zinc Plating or Hot Dip Galvanized



Part No.	Size	ASTM80			NACM90			NACM96			Set/Per Drum
		Weight (kg)	Working Load Limit (lbs.)	Breaking Load (lbs.)	Weight (kg)	Working Load Limit(lbs.)	Breaking Load (lbs.)	Weight (kg)	Working Load Limit(lbs.)	Breaking Load (lbs.)	
TKC036	1/4" * 14'	5.0	2,600	7,500	4.5	2,600	7,500	4.5	2,600	7,500	50
TKC037	1/4" * 16'	6.0	2,600	7,500	5.0	2,600	7,500	5.0	2,600	7,500	40
TKC038	5/16" * 14'	7.5	3,900	11,600	6.0	3,900	9,700	7.0	3,900	11,700	35
TKC039	5/16" * 16'	8.5	3,900	11,600	6.8	3,900	9,700	8.0	3,900	11,700	30
TKC040	5/16" * 18'	9.5	3,900	11,600	7.5	3,900	9,700	9.0	3,900	11,700	30
TKC041	5/16" * 20'	10.5	3,900	11,600	8.0	3,900	9,700	9.5	3,900	11,700	25
TKC042	5/16" * 25'	13.0	3,900	11,600	10.0	3,900	9,700	12.0	3,900	11,700	20
TKC043	5/16" * 30'	15.5	3,900	11,600	12.0	3,900	9,700	14.0	3,900	11,700	20
TKC044	3/8" * 14'	10.5	5,400	16,200	9.5	5,400	15,200	10.0	5,400	16,200	25
TKC045	3/8" * 16'	12.0	5,400	16,200	11.0	5,400	15,200	11.5	5,400	16,200	25
TKC046	3/8" * 20'	15.0	5,400	16,200	13.5	5,400	15,200	13.5	5,400	16,200	20
TKC047	3/8" * 25'	18.5	5,400	16,200	16.5	5,400	15,200	17.5	5,400	16,200	20

8. Chain with Clevis/ Eye Grab Hooks on Both Ends (G70)

G70 Chain
 Material: Alloy Steel(20mn2)
 Heat Treatment: Yes
 Surface: Zinc Plating or Hot Dip Galvanized



Part No.	Size	ASTM80			NACM90			NACM96			Set/Per Drum
		Weight(kg)	Working Load Limit (lbs.)	Breaking Load (lbs.)	Weight (kg)	Working Load Limit (lbs.)	Breaking Load (lbs.)	Weight (kg)	Working Load Limit (lbs.)	Breaking Load(lbs.)	
TKC048	1/4" * 14'	5.0	3,150	12,600	4.5	3,150	12,100	4.5	3,150	12,600	50
TKC049	1/4" * 16'	6.0	3,150	12,600	5.0	3,150	12,100	5.0	3,150	12,600	40
TKC050	5/16" * 14'	7.5	4,700	18,800	7.0	4,700	18,800	7.0	4,700	18,800	35
TKC051	5/16" * 16'	8.5	4,700	18,800	8.0	4,700	18,800	8.0	4,700	18,800	30
TKC052	5/16" * 18'	9.5	4,700	18,800	9.0	4,700	18,800	9.0	4,700	18,800	30
TKC053	5/16" * 20'	10.5	4,700	18,800	10.0	4,700	18,800	10.0	4,700	18,800	25
TKC054	5/16" * 25'	13.0	4,700	18,800	12.0	4,700	18,800	12.0	4,700	18,800	20
TKC055	5/16" * 30'	15.5	4,700	18,800	14.5	4,700	18,800	14.5	4,700	18,800	20
TKC056	3/8" * 14'	10.5	6,600	26,400	9.5	6,600	24,700	10.0	6,600	26,400	25
TKC057	3/8" * 16'	12.0	6,600	26,400	11.0	6,600	24,700	11.5	6,600	26,400	20
TKC058	3/8" * 20'	15.0	6,600	26,400	13.6	6,600	24,700	14.5	6,600	26,400	20
TKC059	3/8" * 25'	18.5	6,600	26,400	16.5	6,600	24,700	18.0	6,600	26,400	15

9. Grade 80 Alloy Chain

G80 Chain
 Material: Alloy Steel(20mn2)
 Heat Treatment: Yes
 Surface: Black Oxide Coating



Part No.	Size(mm)	Working Load Limit(t)	Breaking Strength (t)	Weight Per M (kg)	Inside Length (mm)	Inside Width (mm)
TKC060	6	1.15	4.6	0.8	18	8.7
TKC061	7	1.57	6.3	1.08	22	10.7
TKC062	8	2.05	8.2	1.43	24	12
TKC063	9	2.5	10.4	1.8	27	12
TKC064	10	3.2	12.8	2.22	30	14.5
TKC065	13	5.4	21.8	3.73	39	19
TKC066	13	5.4	21.8	2.9	42	23
TKC067	16	8.2	32.9	5.58	48	24
TKC068	19	11.2	46.3	8	57	26
TKC069	20	12.5	51	9	60	28
TKC070	22	15	61.2	10.9	66	29.5
TKC071	26	20	81.6	15.2	78	35

10. Grade 80 Alloy Chain

G80 Chain
 Material: Alloy Steel(20mn2)
 Heat Treatment: Yes
 Surface: Powder Painted



Part No.	Chain Size(mm)	Working Load Limit(t)	Breaking Strength (t)	Weight Per M (kg)	Inside Length (mm)	Inside Width (mm)
TKC072	6	2.3	4.5	0.64	35	22
TKC073	9	5	10	1.42	53	33
TKC074	11	7.5	15	2.18	64	40
TKC075	13	9.7	19.4	3.01	80	48

Chain

1.1. Grade 100 Alloy Chain

G100 Chain

Material: Alloy Steel

Heat Treatment: Yes

Surface: Powder Painted



Part No.	Chain Size(mm)	Working Load Limit(t)	Breaking Strength (t)	Weight Per M (kg)	Inside Length (mm)	Inside Width (mm)
TKC076	6	1.4	5.7	0.8	18	9
TKC077	7	1.95	7.8	1.09	21	10.5
TKC078	8	2.6	10.4	1.43	24	12
TKC079	10	4	16.2	2.23	30	15
TKC080	12	5.65	22.6	3.21	36	18
TKC081	13	6.8	27.4	3.77	39	19.5
TKC082	16	10.3	41	5.71	48	24
TKC083	18	13	51.9	7.23	54	27
TKC084	19	14.4	57.8	8.04	57	28.5
TKC085	20	16	64.2	8.92	60	30
TKC086	22	19.4	77.7	10.8	66	33

1.2. DIN5685A/C Short/Long Link Chain



Part No.	Size(mm)	Inside Length (mm)	Outside Width (mm)	Weight Per 100M (kg)	Working Load Limit(n)	Breaking Load (n)	Grade
TKC087	6	24	24	73	4,500	11,500	A
TKC088		42		63			C
TKC089	6.5	26	26	86	5,400	13,500	A
TKC090		45.5		74			C
TKC091	7	28	28	100	6,000	15,000	A
TKC092		49		86			C
TKC093	8	32	32	130	8,000	20,000	A
TKC094		52		110			C
TKC095	8.5	34	34	149	9,000	22,500	A
TKC096		56		125			C
TKC097	9	36	36	165	10,000	25,000	A
TKC098		59		141			C
TKC099	10	40	40	205	12,500	31,000	A
TKC100		65		175			C
TKC101	11	44	44	250	15,000	38,000	A
TKC102		72		211			C
TKC103	12	48	48	290	18,000	45,000	A
TKC104		78		255			C
TKC105	13	52	52	345	21,200	53,000	A
TKC106		82		295			C

1.3. DIN763 Link Chain



Part No.	Size		Inside Length		Outside Width		Weight Per M (kg)	Working Load Limit(kg)	Test Load (kn)	Breaking Load (kn)
	mm	±mm	mm	±mm	mm	±mm				
TKC107	6	0.5	42	2.0	24	1.2	0.63	224	4.5	14.0
TKC108	7		49	2.5	28	1.4	0.86	300	6.0	18.0
TKC109	8		52	2.5	32	1.6	1.1	400	8.0	22.5
TKC110	8.5		56	2.8	34	1.7	1.25	460	9.0	25.0
TKC111	9		59	3.0	36	1.8	1.41	530	10.5	32.0
TKC112	10	1.0	65	3.2	40	2.0	1.75	630	12.5	40.0
TKC113	11		72	3.4	44	2.0	2.11	790	15.8	47.5
TKC114	12		78	3.6	48	2.3	2.55	940	18.8	56.5
TKC115	13		82	4.0	52	2.5	4.45	1,000	21.2	63.0
TKC116	16		100	5.0	64	3.2	5.95	1,600	33.0	100.0
TKC117	18		113	5.2	70	3.2	6.25	2,120	42.3	127.0
TKC118	19		119	5.6	72	3.4	6.65	2,370	47.3	142.0
TKC119	20		120	6.0	75	3.8	7.00	2,500	50.0	160.0
TKC120	22		127	6.0	82	4.0	8.55	3,170	63.3	190.0
TKC121	25		140	6.6	85	4.2	10.90	4,090	81.7	245.0
TKC122	28		152	7.0	96	4.7	13.90	6,000	120.0	300.0
TKC123	32		171	7.8	108	5.2	18.20	8,000	160.0	400.0

1.4. DIN764 Link Chain



Part No.	Size		Inside Length		Inside Width (mm)	Outside Width (mm)	Length Per 11 Link		Weight Per 100M (kg)	Breaking Load (n)
	mm	±mm	mm	±mm			mm	±mm		
TKC124	6	0.2	21	0.5	8	21.5	231	2.0	74	16.5
				0.2				1.1		
TKC125	8	0.2	28	0.5	11	29	308	2.2	131.5	32
				0.3				1.2		
TKC126	10	0.3	35	0.6	14	36	385	2.8	200	500
				0.3				1.5		
TKC127	12	0.3	42	0.6	16	41	462	3.2	298	70
				0.3				1.8		
TKC128	13	0.4	45	0.7	18	47	495	3.5	350	80
				0.4				2.0		
TKC129	14	0.45	49	0.75	20	48	539	3.8	406	92
				0.45				2.0		
TKC130	16	0.5	56	0.9	22	58	616	4.3	520	125
				0.5				2.5		
TKC131	18	0.8	63	1.0	24	65	693	4.7	650	160
				0.5				2.8		
TKC132	20	1.0	70	1.1	27	72	770	5.4	820	200
				0.6				3.2		
TKC133	23	1.2	80	1.3	31	83	880	6.2	1100	250
				0.7				3.5		
TKC134	26	1.3	91	1.5	35	94	1001	7.0	1400	320
				0.8				4.0		

Chain



15. DIN766 Link Chain

Part No.	Size		Inside Length			Inside Width (mm)	Outside Width (mm)	Length Per 11 Link			Weight (kg)	Breaking Load (n)
	mm	±mm	mm	+mm	-mm			mm	+mm	-mm		
TKC135	6	0.2	18.5	0.4	0.2	7.2	20.2	203.5	2.4	1.2	0.8	16
TKC136	7	0.3	22	0.4	0.2	8.4	23.8	242	3	1.4	1.1	25
TKC137	8	0.3	24	0.4	0.2	9.6	27.2	264	3.2	1.5	1.4	32
TKC138	9	0.4	27	0.5	0.3	10.8	30.6	297	3.6	1.8	1.8	40
TKC139	10	0.4	28	0.5	0.3	12	34	308	3.7	1.9	2.2	50
TKC140	11	0.4	31	0.5	0.3	13.2	37.4	341	4.0	2	2.7	63
TKC141	12	0.5	35	0.6	0.3	14.4	40.8	396	4.4	2.2	3.1	71.5
TKC142	13	0.5	36	0.6	0.3	15.6	44.2	396	4.6	2.4	3.8	80
TKC143	14	0.6	41	0.7	0.4	16.8	47.6	451	5.4	2.7	4.4	100
TKC144	16	0.6	45	0.8	0.4	19.2	54.4	495	6	3	5.7	125
TKC145	18	0.9	50	0.8	0.4	21.6	61.2	550	6.6	3.3	7.3	160
TKC146	19	0.9	53	0.9	0.4	22.8	64.6	583	7	3.7	7.9	180
TKC147	20	1.0	56	1.0	0.5	24	68	616	7.4	3.7	9	200
TKC148	22	1.2	62	1.1	0.5	26.4	75	682	8	4	11	232
TKC149	23	1.2	64	1.1	0.5	27.6	78.2	704	8.4	4.2	12	250
TKC150	26	1.3	73	1.2	0.6	31.2	88.4	803	9.6	4.8	15	320
TKC151	28	1.4	78	1.3	0.65	33.8	95.2	858	10.2	5.1	18	-



16. Australian Short Link Chain

Part No.	Size(mm)	Working Load Limit(t)	Inside Length (mm)	Inside Width (mm)	Links per M	Length (M) per 100KG	
						pc	B.F.
TKC212	5	0.24	17.2	14.6	68.3	174	167
TKC213	6	0.32	21.5	18.9	52.9	114	108
TKC214	8	0.53	27.5	24	41.7	70.5	67
TKC215	10	0.83	33.5	29.5	33.9	45.2	42.9
TKC216	12	1.5	40.6	37.5	26.7	29.5	28
TKC217	13	1.6	44.6	38.8	25.8	26.9	26.3
TKC218	16	2.31	54	47	21.3	17.6	16.7
TKC219	20	3.45	68.5	59.2	16.9	11.3	11.1
TKC220	22	4.55	77	64.9	15.4	9.5	9.2
TKC221	24	5.43	82.2	71	14.1	7.8	7.6



17. Australian Medium Link Chain

Part No.	Size(mm)	Working Load Limit(t)	Inside Length (mm)	Inside Width (mm)	Links per M	Length (M) per 100KG	
						pc	B.F.
TKC222	3	0.06	15.7	13.1	63.8	511	498
TKC223	4	0.11	18.6	16	53.9	320	305
TKC224	5	0.19	22	19.4	45.4	203	193
TKC225	6	0.32	26.1	23.5	37.8	129	120
TKC226	8	0.53	32.2	29.5	31	77.8	74.1
TKC227	10	0.83	39.1	36.2	25	48.5	47.1
TKC228	12	1.35	46	44	21.7	34	33.3
TKC229	13	1.5	49.1	46.1	20.3	29.7	27.7
TKC230	16	2.31	59.6	56.5	16.8	20.2	18.2
TKC231	20	3.67	73.3	70	13.6	12.3	11.6
TKC232	24	5.31	87	83.6	11.5	8.5	8.04

Chain

18. Tow Chain



Part No.	Size	W.L.L. (lbs.)	MBS (lbs.)	Weight (kg)
262	5/16"*24'	6580	26320	7.86

19. Tow Chain



Part No.	Size	W.L.L. (lbs.)	MBS (lbs.)	Weight (kg)
263	5/16"*24'	6580	26320	5.32

20. Tow Chain



Part No.	Size	W.L.L. (lbs.)	MBS (lbs.)	Weight (kg)
264	5/16"*24'	6580	26320	7.53